



E7002/E7002(A)/E7002(B)/E7002(C)

Motorized Paperless Interactive Monitor Lift



Product description

Touch paperless intelligent desktop adopts 15.6/17.3/18.5/21.5-inch high-definition widescreen design, which fully conforms to the comfortable visual effect of human sitting posture at the conference site. The height is strictly designed according to the angle of unobstructed sight. It is equipped with an integrated lifter, which is connected seamlessly and without backplane, highlighting the high-end atmosphere of the product; With the paperless conference terminal, it perfectly realizes the interactive paperless powerful conference function.

Features

1. Touch ultra-thin high-definition display shell aluminum alloy material, surface treatment for sandblasting anodizing, ultra-thin LCD screen design.
2. The 15.6/17.3/18.5/21.5-inch multi-point capacitive touch HD LCD screen is adopted, with a resolution of 1920 × 1080 dpi. The screen viewing angle is IPS full-view LCD screen, with clear and bright display effect.
3. Lifter panel is made of aviation aluminum, anodized wiredrawing process, ultra-thin design, panel width is only 80mm.
4. The touch ultra-thin high-definition display screen and the ultra-thin round shaft lifter have no exposed connecting wires, no connecting backplane, and no exposed screws, which ensures that the lifting display touch screen is beautiful and elegant as a whole.
5. The lifter supports 232, 485 control, software control and manual control. The control software supports PC installation and is compatible with common operating systems. It can be controlled in a unified way or in any group to control the lifting, pause, lowering and other motion States of the lifter.
6. The lifter panel is equipped with up, pause, down, multimedia conference terminal switch interface; lift support manual elevation angle of 15 degrees, to ensure the best viewing angle of the display and touch angle;



7. With power protection function, the lift desktop panel is preset with USB information interface, support document data import and export.

Technical parameters

Model	Screen size	Panel size (L×H×W)	Box size (L×W×H)	Weight
E7002	15.6"(361*220mm)	428*65*3mm	416*58*600mm	14kg
E7002(A)	17.3"(399*251*8mm)	470*65*3mm	452*58*600mm	14.5kg
E7002(B)	18.5"(430*260*10mm)	500*65*3mm	482*58*640mm	15kg
E7002(C)	21.5"(493*290*16mm)	560*65*3mm	545*58*670mm	15.5kg

Parameter	Specification
Display scale	16:9
Physical resolution	1920×1080
Viewing angle of the display	IPS full viewing angle
Touch screen type	Capacitive screen, 10-point touch
Interface	1×HDMI、1×VGA、2×USB2.0
Work environment	Ambient temperature: 5 °C ~ 40 °C; relative humidity: ≧ 75%
Operating voltage	DC12V
Color	Silver (customizable black)