



E7003/E7003(A)/E7003(B)/E7003(C) Motorized Paperless

Interactive Monitor Lift (with Fixed Microphone)



Product description

Ultra-thin panel design, its appearance is exquisite, high-grade, beautiful, and the desktop of the conference room to achieve perfect unity, easy to use, highlighting the intelligent high-grade conference environment. In order to improve the comprehensive effect of the conference room, the terminal includes a professional conference microphone, which uses a condenser microphone with clear pickup and high reduction. With the paperless conference terminal, the powerful interactive paperless conference function is perfectly realized.

Features

1. Touch ultra-thin HD display shell aluminium alloy material, surface treatment for sandblast anodic oxidation, ultra-thin LCD screen design.
2. Using 15.6/17.3/18.5/21.5-inch multi-point capacitive touch HD LCD screen, the resolution of 1920 × 1080dpi, the screen view for the IPS full-view LCD screen, the display effect is clear and bright.
3. Cardioid directional capacitive pickup, with dual-colour indicator, speak for the red, apply to speak for the flashing green, and can be removed during the intersessional period;
4. Chairman unit with the following conference control functions: approval of the delegate's speech application function; can be forced to close the representative of the speech unit is speaking; not subject to the number of speakers, the limitations of the speech mode, can be freely opened, not subject to the limitations of the installation location; the representative of the unit has a speech application function, subject to the control of the chairman unit.
5. Lifter panel aviation aluminium material, anodic oxidation brushed process, using ultra-thin design, panel width of only 65mm.
6. Touch ultra-thin high-definition display and ultra-thin round shaft lifter without exposed connecting lines, no connection backplane, no exposed screws, to ensure that the lifting display touch screen overall beautiful and generous.



7. Lifter support 232, 485 control, software control, manual control, control software support PC installation, compatible with commonly used operating systems, can be unified control can also be any group control lifter rise, pause, fall and other movement states.

8. Lift panel with: up, pause, down, multimedia conference terminal switch interface; lift support manual elevation angle of 15 degrees, to ensure that the best viewing angle of the display and touch angle.

9. With power protection function, the lift desktop panel is preset with USB information interface, supporting document data import and export.

Technical parameters

Model	Screen size	Panel size (L×H×W)	Box size (L×W×H)	Weight
E7003	15.6"(361*227*8mm)	538*65*3mm	413*600*58mm	14.25kg
E7003(A)	17.3"(399*251*8mm)	580*65*3mm	452*600*58mm	14.75kg
E7003(B)	18.5"(430*260*10mm)	610*65*3mm	482*600*58mm	15.25kg
E7003(C)	21.5"(493*290*16mm)	670*65*3mm	545*670*58mm	15.75kg

Parameter	Specification
Display scale	16:9
Physical resolution	1920×1080
Viewing angle of the display	IPS full viewing angle
Touch screen type	Capacitive screen, 10-point touch
Interface	1×HDMI、1×VGA、2×USB2.0
Work environment	Ambient temperature: 5°C ~ 40°C; relative humidity: ≧ 75%
Operating voltage	DC12V
Color	Silver (customizable black)