



E7005/E7005(A)/E7005(B)/E7005(C) Motorized Paperless Interactive Monitor Lift (With 10.1" Rear LCD Screen)



Product description

Ultra-thin panel design, its appearance is exquisite, high-grade, beautiful, and the desktop of the conference room to achieve perfect unity, easy to use, highlighting the intelligent high-grade conference environment. In order to improve the comprehensive effect of the conference room, the terminal screen is a dual-screen display, and the main screen is combined with the electronic table card. The main screen is used as the function screen of the conference application, and the secondary screen is used to display the names of the participants. With the paperless conference terminal, the interactive paperless powerful conference function is perfectly realized.

Features

1. Touch ultra-thin HD display shell aluminium alloy material, surface treatment for sandblast anodic oxidation, ultra-thin LCD screen design.
2. Using 15.6/17.3/18.5/21.5-inch multi-point capacitive touch HD LCD screen, resolution of 1920 × 1080dpi, the screen view for the IPS full-viewing angle LCD screen, the display effect is clear and bright.
3. Sub-screen with 10.1-inch LCD screen, do electronic nameplate use, can be customized background image, resolution 1024 × 600dpi;
4. Lift panel made of aviation aluminium, anodic oxidation brushed process, with ultra-thin design, the panel width is only 65mm.
5. Touch ultra-thin high-definition display and ultra-thin round shaft lifter without exposed connecting lines, no connection backplane, no exposed screws, to ensure that lifting the display touch screen overall beautiful and generous.
6. Lifter support 232, 485 control, software control, manual control, control software support PC installation, compatible with commonly used operating systems, can be unified control can also be any group control lifter rise, pause, fall and other movement states.



7. Lift panel with: up, pause, down, multimedia conference terminal switch interface; lift support manual elevation angle of 15 degrees, to ensure that the best viewing angle of the display and touch angle.
8. With power protection function, lifter desktop panel is preset with USB information interface, support document data import and export.
9. Strong and weak power separation, using a wide voltage adapter power supply.
10. Angle can be swung electrically or the angle can be manually triggered.
11. The lift will automatically descend when it encounters obstacles in the process of ascending.

Technical parameters

Model	Screen size	Panel size (L×H× W)	Box size (L× W × H)	Weight
E7005	15.6"(361*220mm)	428*65*3mm	413*58*600mm	14.5kg
E7005(A)	17.3"(399*251mm)	470*65*3mm	452*58*600mm	15kg
E7005(B)	18.5"(430*260mm)	500*65*3mm	482*58*640mm	15.5kg
E7005(C)	21.5"(493*290mm)	560*65*3mm	545*58*670mm	16kg

Parameter	Specification
Display scale	16:9
Physical resolution	1920×1080
Viewing angle of the display	IPS full viewing angle
Touch screen type	Capacitive screen, 10-point touch
Interface	1×HDMI、1×VGA、1×USB2.0
Work environment	Ambient temperature: 5 °C ~ 40 °C; relative humidity: ≧ 75%
Operating voltage	DC12V
Color	Silver (customizable black)