



E7007/E7007(A)/E7007(B)/E700(C) Alta-thin Paperless

Capactive Flippable LCD Screen (0-120° flip)



Product description

The embedded flip all-in-one machine is specially developed to solve the problem of display occlusion in traditional conferences. It adopts a composite flip structure, and the main part of the display is hidden in the desktop content, which can realize the free flip of 0-120 degrees. Standard keyboard and mouse, all operations can be completed through the use of keyboard and mouse habits. The keyboard and mouse are built into the body and flip out at the same time as the screen. With the paperless conference terminal, the powerful interactive paperless conference function is perfectly realized.

Features

1. Embedded flip all-in-one housing aluminium alloy material, surface treatment for sandblast anodic oxidation, flip design.
2. Using 15.6/17.3/18.5/21.5-inch high-definition LCD screen, resolution of 1920 × 1080dpi, the screen view for the IPS full-viewing angle LCD screen, the display effect is clear and bright.
3. Embedded flip all-in-one without exposed connection lines, no connection backplane, no exposed screws, to ensure that the lift display touch screen overall appearance.
4. Flip all-in-one machine support 232, 485 control, software control, manual control, control software support PC installation, compatible with commonly used operating systems, can be a unified control can also be any group control lift up, pause, down and other movement states.
5. Flip all-in-one machine with: rise, pause, fall, multimedia conference terminal switch interface;
6. With power protection function, lifter desktop panel preset USB information interface, support document data import and export.
7. With strong and weak power separation, using a wide voltage adapter power supply.



8. The angle can be swung electrically or the angle can be manually triggered.
9. The lift will automatically descend when it encounters obstacles in the process of ascending.

Technical parameters:

Model	Screen size	Panel size (L×W×T)	Box size (L×W×H)	Weight
E7007	15.6"	430*360*5mm	412*346*120mm	14.5kg
E7007(A)	17.3"	465*390*5mm	450*375*120mm	15kg
E7007(B)	18.5"	515*415*5mm	499*400*120mm	15.5kg
E7007(C)	21.5"	560*430*5mm	545*415*120mm	16kg

Parameter	Specification
Display scale	16:9
Physical resolution	1920×1080
Viewing angle of the display	IPS full viewing angle
Touch screen type	None
Interface	1×HDMI、1×VGA、1×USB2.0
Work environment	Ambient temperature: 5 °C ~ 40 °C; relative humidity: ≧ 75%
Operating voltage	DC12V
Color	Silver (customizable black)