



## E7018/E7018(A)/E7018(B)/E7018(C) Motorized Paperless Interactive Monitor Lift (with lifted microphone)



### Product description

Ultra-thin panel design, its appearance is exquisite, high-grade, beautiful, and the desktop of the conference room to achieve perfect unity, easy to use, highlighting the intelligent high-grade conference environment. With integrated microphone lifting function and paperless conference terminal, it perfectly realizes interactive paperless and powerful conference function.

### Features

1. Touch ultra-thin HD display shell aluminium alloy material, surface treatment for sandblast anodic oxidation, ultra-thin LCD screen design.
2. Using 15.6/17.3/18.5/21.5-inch multi-point capacitive touch HD LCD screen, the resolution of 1920 × 1080dpi, the screen view for the IPS full-view LCD screen, the display effect is clear and bright.
3. Heart-shaped directional capacitive pickup with dual-colour indicator, speak for the red, apply to speak for the flashing green, can be lifted and lowered with the lifter, to keep the desktop clean;
4. The chairman unit has the following conference control functions: approval of the delegate's speech application function; can be forced to close the representative of the speech unit is speaking; not subject to the number of speakers, the limitations of the speech mode, can be freely opened, not subject to the limitations of the installation location; the representative of the unit has a speech application function, subject to the control of the chairman unit.
5. Lifter panel made of aviation aluminium, anodic oxidation brushed process, the use of ultra-thin design, panel width of only 65mm.
6. Products equipped with microphone lifter, can achieve a healthy microphone lifting function, with the conference host to achieve the hand-to-hand conference speech;
7. Touch ultra-thin high-definition display and ultra-thin round axis lift without exposed connecting wires, no connection to the backplane, no exposed screws, to ensure that lifting the display of the touch screen as a whole beautiful and generous.



8. Lifter support 232, 485 control, software control, manual control, control software support PC installation, compatible with commonly used operating systems, can be unified control can also be any group control lifter rise, pause, fall and other movement states.

9. Lift panel with: up, pause, down, multimedia conference terminal switch interface; lift support manual elevation angle of 15 degrees, to ensure that the best viewing angle of the display and touch angle.

10. With power protection function, lifter desktop panel is preset with USB information interface, support document data import and export.

11. Strong and weak power separation, using a wide voltage adapter power supply.

12. Angle can be swung electrically or the angle can be manually triggered.

13. The lift will automatically descend when it encounters obstacles in the process of ascending.

### Technical parameters

Model	Screen size	Panel size (L×W×T)	Box size (L×W×H)	Weight
E7018	15.6"(361*227*8mm)	555*65*3mm	535*58*680mm	14.25kg
E7018(A)	17.3"(399*251*8mm)	600*65*3mm	575*58*680mm	14.75kg
E7018(B)	18.5"(430*260*10mm)	625*65*3mm	605*58*730mm	15.25kg
E7018(C)	21.5"(493*290*16mm)	690*65*3mm	668*58*730mm	15.75kg

Parameter	Specification
Display scale	16:9
Physical resolution	1920×1080
Viewing angle of the display	IPS full viewing angle
Touch screen type	Capacitive screen, 10-point touch
Interface	1×HDMI、1×VGA、2×USB2.0
Work environment	Ambient temperature: 5 °C ~ 40 °C; relative humidity: ≥ 75%
Operating voltage	DC12V
Color	Silver (customizable black)