



## E7040 Paperless Intelligent Control Host



### Features:

1. 4U industrial grade 19-inch standard rack temperature control server cabinet installation.
2. The equipment is equipped with a display screen to display the equipment temperature in real time.
3. The intelligent conference terminal is managed centrally and effectively through the network, and the terminal can be managed in one or more high-end conference rooms, so as to improve the ability of interactive transmission, management and information backup of conference information in the conference system;
4. The equipment contains conference background management software, which can be directly accessed and controlled through WEB in the network, and supports unattended function;
5. Support multi-conference room management, support multi-conference presetting, support conference scheduling, support LAN and external network connection and communication, and support powerful conference management functions;
6. Support the user-defined construction of personnel database, create the organizational structure according to personnel information, and set the association by three levels of departments. Edit relevant personnel information and participation authority, set independent password to realize password login function, upload corresponding personnel image information, and realize face recognition check-in function
7. For conference materials, you can add, modify and delete conference directory information, and set directory permissions for participants; Import, modify and delete files, and sort files; The information change is updated to the client in real time; Support the temporary addition, deletion and modification of files in the meeting, and update to the client in real time.

**Specification:**

CPU	Intel i5 4570
Memory	8GDDR3
Storage hard disk	1T
Network card	Gigabit Network Interface (RJ45)
Video output connector	HDMI×1, VGA×1
Audio interface	1 × 3.5mm audio input interface, 1 × 3.5mm audio output interface, 1 × 3.5mmMIC interface
Control interface	1 × serial port, 6 × USB interface
Work environment	Ambient temperature: 5 °C ~ 40 °C; Relative humidity: ≤ 75%
Operating power consumption	AC300W+
Support wide voltage	110-240V, 50/60Hz
Operating System	Support windows, domestic Kirin system, LX system and other multi-system deployment
Chassis dimensions (W * H * D)	484*176*450mm
Craft	Anodized treatment, exquisite and beautiful
Material	Surface treatment tinplate, anodized front panel black and white two-tone aluminum wiredrawing