



## Multimedia Active Speaker SA-245BV



### Features:

1. Wall-mounted design, delicate and beautiful, exquisite craftsmanship, easy to install.
2. Operating frequency band: UHF band.
3. Built-in 2x20W power amplifier module, drive the built-in high-fidelity speakers, sound quality is delicate.
4. 2.1-channel multimedia speakers, 1 microphone input, 1 line input. Mixer volume, treble volume, master volume can be adjusted independently.
5. Built-in 1-way power output, external sub-speaker. ■ Integrated 24Bit professional-grade sound card for audiophile-grade audio playback, with a maximum audio stream of 768kpbs.
6. Microphone switch with light touch button design, long time no signal state with automatic shutdown function, to avoid battery loss and damage caused by forgetting.
7. The microphone is equipped with LCD display, which can show the working condition of the device.
8. Power on automatically search for clean channels and automatic pairing, through the infrared frequency pairing, to ensure the uniqueness of the pairing device, to ensure that the product does not crosstalk, anti-jamming, stable transmission;
9. Built-in rechargeable high-performance 3.7V lithium polymer battery. Battery capacity: 340mA, with protection circuit, safe and reliable, Type C interface charging, 2 hours fully charged can last  $\geq 8$ h.
10. Built-in antenna, more convenient installation, more stable performance.
11. Support optional PPT page flip and a key black screen / recovery function, can be used with a projector or computer display explanation. PPT page flip module supports hot-swap, no need to install driver software..



### Technical Parameter

Model	SA-245BV
Audio mode	16 bit CD quality
sampling rate	16K~48KHz
AUX Input	1 group
AUX sensitivity	250mV
MIC input	2 groups
MIC sensitivity	5mV
Output Power	20W×2
Paired speaker output	1 group
Line Output level/impedance	775mV/1KΩ
Power Consumption	30W
Frequency response	80Hz-16KHz -3dB/+1dB
Harmonic distortion	THD≤0.3%
Signal to noise ratio	≥90dB
Product size	190×175×280 mm
Weight	3.2Kg