



## SA-2A180 Educational Multimedia Power Amplifier



### Product features

- Aluminum alloy panel, surface wiredrawing process, simple and elegant appearance, 4-channel input options, more convenient to switch when using multiple sound supply devices.
- This machine is also equipped with short-circuit protection and DC protection functions, which can protect the speaker more effectively. Loop air-cooled design.
- Precise amplification capability for true reproduction of sound density.
- Multi-channel audio input, 2-channel line input, 3-channel microphone input, independently adjustable volume, also equipped with total volume control.
- Fully enclosed high-density copper radiator, intelligent high-speed fan system, to ensure long-term safe operation of the amplifier, suitable for a variety of harsh environments.
- The product can realize microphone effect, mixing, delay, high, middle and bass adjustment functions.
- The system has MP3 playing function, and can be connected to USB/SD card for music playing.
- Each channel has pressure limit control function.

### Technical parameters

Model	SA-2A180
Power 8 ohms	2×180W
Power 4 ohms	2×320W
Input impedance	20k0hm
Total harmonic distortion	<0.05%
Frequency response	20Hz-20KHz(+/-0.5dB)
Signal to noise ratio	82dB
Power consumption	500W
Input sensitivity	0.35V
Cooling	Intelligent stepless variable speed circuit
Amplified protection	Overheating, short circuit, DC
Size	440×430×132mm
Outer box size	600×550×230mm