

SA-4S60/SA-4S120/SA-4S180/SA-4S240

Four-channel Power Amplifier



Features

1. Standard cabinet design (2U), humanized design, black aluminum alloy wire drawing process, showing high-grade temperament.
2. 4-channel unbalanced RCA terminal input.
3. The panel with control knob controls the volume of 4 channels respectively.
4. The product has short circuit, overload, overheating self-protection.
5. Each channel has two power output modes: constant voltage output 100 V, 70 V and constant resistance output 4 ~ 16 Ω .

Technical parameters

Model	SA-4S60	SA-4S120	SA-4S180	SA-4S240
Rated output power	4×60W	4×120W	4×180W	4×240W
Power consumption	400W	720W	1100W	1500W
Speaker output	70V, 100V & 4~16 Ω			
Input sensitivity	775 mV/10 K Ω , unbalanced RCA input terminals			
Overload source electromotive force	> 15dB			
Frequency response	50~16KHz(+1dB, -3dB)			
Signal to noise ratio	> 90dB			
Total harmonic distortion	0.5% at 1 KHz, 1/3 output power			
Channel crosstalk	< 50dB			



attenuation				
Heat dissipation	Forced air cooling from front to back, start the built-in fan when the radiator temperature is 55 degrees.			
Protect	Overheat, overload & short circuit			
Power supply	~220V/50Hz			
Size	484×448×88mm			
Weight	17.6Kg	21.5Kg	28Kg	30.2Kg