



## SA-7006(D) Two-Key Alarm (Help) Voice Intercom Panel



### Features:

1. It adopts all-aluminum alloy design, IP65 high protection grade
2. High-reliability circuit design, with power and network double lightning surge protection capability, up to GB/T 17626. 5, the highest level 4 standard
3. Two red LED light ring metal button for one-key alarm or one-key help;
4. Built-in 5 W speaker and high-sensitivity microphone;
5. It has a 30 W power amplifier output port, which can be connected to an 8 ohm 30 W speaker
6. With two-way linkage input and two-way linkage output interface, it is convenient for linkage expansion with other systems;
7. Broadcast sound source output with one way of sound mixing, used for broadcast amplification of external power amplifier;
8. With a 24V active pickup interface, it can be used for monitoring input expansion;



### Technical parameters:

Power source	24V/2A
Network interface	Standard RJ45
Power output	30W/8Ω
Standby power	< 1W
Maximum operating power	< 50W
MIC sensitivity	10mV/600Ω
Frequency response	20Hz~20KHz
Signal to noise ratio	≥80dB
Sampling rate	16K~48KHz
Audio bit rate	8Kbps ~ 320Kbps adaptive
Audio format	MP3
Total harmonic distortion	≤0.1%
Transmission rate	10/100Mbps
Network protocol	ARP, UDP, TCP/IP, ICMP, IGMP (Multicast)
Broadcast delay	≤50ms
Operating ambient temperature	-20°C ~ +60°C
Humidity of working environment	10%~90%
Dimension (mm)	194 (H) × 108 (W) × 58.5 (D)
Weight	0.85kg
Degree of protection	IP65