



SA-7021 Rack-Mounted IP Network Broadcast Terminal



Features:

1. 19-inch standard rack, 1U height;
2. The fixed static IP address is adopted. When the network changes, the address will not be lost and the operation is stable;
3. Sound quality reaches CD level (audio file bit rate is 8-320kbps adaptive);
4. Automatically control the power supply of external power amplifier equipment;
5. Receiving audio program content by network;
6. Provide automatic/manual forced power switch button;
7. Remote network signal priority, automatic forced insertion;
8. Built-in network switch module;

Technical parameters:

Power source	AC 110/115/120/220/230/240V,50-60Hz
Output Sensitivity & Source Impedance	0.775V/600Ω
Audio bit rate	8Kbps ~ 320Kbps adaptive
Frequency response	20Hz~20KHz (±3dB)
Signal to noise ratio	≥80dB
Audio format	MP3
Total harmonic distortion	≤1%
Transmission rate	10M/100Mbps
Support agreement	ARP, UDP, TCP/IP, ICMP, IGMP (Multicast)
Standby power	Less than 0.3 W
Output power	500W
Operating temperature	-20℃ ~ +60℃
Operating humidity	10% ~ 90%
Dimension (mm)	484 (W) × 180 (D) × 44 (H)
Weight	2.3kg