



## SA-7030P/SA-7060P IP Network Broadcast Column Speaker



### Features:

1. Integrated design of digital decoding terminal and column speaker, aluminum alloy waterproof and rust-proof shell structure, wall-mounted installation, suitable for long-term outdoor work;
2. With one 10/100MRJ45 network switch interface, supporting LAN and WAN;
3. Timed task function is supported, and audio program content can be received through the network.
4. Support IP address reset, long press for more than 3s to restore factory settings;
5. With overheat, overvoltage and overload protection measures, rain-proof and moisture-proof functions.
6. Built-in digital power amplifier module, 30 W/60 W amplifier output.
7. Audio files support MP3 format.
8. It has certain lightning protection function.

### Technical parameters:

Model	SA-7030P	SA-7060P
Power output	30W	60W
Network interface	Group 1 RJ45	
Transmission rate	100Mbps/10Mbps	
Support agreement	ARP, UDP, TCP/IP, ICMP, IGMP (multicast);	
Audio format	MP3	
Sampling rate	8K~48K	



Frequency response	20Hz—20KHz	
Total harmonic distortion	≤10%;	
Signal to noise ratio	≥90dB	
Protection Circuit	Overload, over-temperature and short-circuit protection circuit	
Supply voltage	AC110/115/120/220/230/240V,50-60Hz	
Work environment	Working temperature: -20 °C ~ + 60 °C; Operating humidity: 10% ~ 90%	
Dimension (mm)	438 (H) × 225 (W) × 120 (T)	700 (H) × 225 (W) × 120 (T)
Weight	4.3kg	6.8kg