



## SC-3212C/SC-3212D Conference Chairman Unit /Delegate Unit



### Product Description

Full-digital conference system discussion unit that supports desktop and embedded two installation methods, with speech discussion, timed speech, application for speech, meeting sign-in, and with LCD screen display.

### Features

1. Independent research and development PA-STREAM digital audio stream processing technology, the sound quality is richer and clearer.
2. CR&MP (Conductive rubber and metal paint) processing technology to avoid the interference of RF signals such as telephones and other wireless when picking up sound.
3. Novel, fashionable appearance, ergonomic design, with design patent, support desktop or embedded flexible installation;
4. Adopt special 8-core high-density aviation connector, come with 2-meter connecting cable, "T-type" connection mode, to ensure reliable connection;
5. Cardioid directional condenser pickup, with two-color indicator light, red when speaking, flashing green when applying to speak;
6. § 3.5mm stereo headphone jack to connect headphones, high-fidelity dual speakers, adjustable volume;
7. The function of suppressing howling, when the microphone is turned on, the built-in speaker is automatically turned off to prevent the sound from returning;
8. With camera tracking system & central control system, it can realize automatic camera tracking function;
9. Microphone stem L: 420mm (standard configuration);
10. Support speech timing and key sign-in functions;
11. High-brightness LCD display in Chinese and English, which can display check-in results and speaking time in real time
12. microphone on/off, real-time check-in number and other information;
13. The chairman unit has the following conference control functions: the function of approving the speech application of the representative; the speaking unit of the representative who is speaking can be forcibly closed, not limited by the number of



speakers and the speaking mode, and can be opened freely, regardless of the installation position; the representative unit has The speech application function is controlled by the chairman unit.

#### **Technical Parameter**

Power supply	DC24V (Power supply by conference host)
Signal-to-noise ratio	>80dB
Channel crosstalk	>80dB
Frequency response	20Hz-20KHz
Total harmonic distortion	<0.05%
Maximum power consumption	1.5W
Control display	16 characters X2 lines (white text on blue background)
Unit interface	8 cores head T-type connection
Color	dark grey
Dimensions (mm)	160L X 160W X 55H