



SC-3218C/SC-3218D Embedded Digital Conference Chairman / Delegate Unit (With voting function)



Chairman unit SC-3218C



Delegate unit SC-3218D

Product Description

The embedded design does not occupy a lot of desktop space. It is connected hand in hand through the CAT6 (CAT6E) network cable to form an embedded conference speaking and voting system.

Features

1. With digital audio stream processing technology, the sound quality is richer and clearer;
2. Adopt exclusive design and processing technology to avoid the interference of RF signals such as telephones and other wireless signals when picking up sound;
3. Embedded design, the panel is made of brushed aluminum black, and the appearance is simple and beautiful;
4. Support timed speech, key sign-in, 3-key/5-key voting functions; Multiple voting forms: yes/abstain/against; Election: choose one candidate from five candidates (1/2/3/4/5); Rating: scoring method (--/ -0/+ /++);
5. High-brightness OLED English display screen, which can display in real time: volume adjustment, microphone on/off, speaking time, real-time sign-in number, voting results and other information; voting & sign-in process related information;
6. ϕ 3.5mm stereo headphone jack to connect headphone, the volume is adjustable;
7. The unit has USB charging (5V~1A), which can charge smartphones and tablets;
8. Cardioid directional condenser pickup, with two-color indicator light, red when speaking, flashing green when applying to speak, and removable during recess;
9. Microphone stem L: 420mm (standard configuration);
10. Improve the stability of the system by reducing the interference of strong electromagnetic waves on the wire;



11. "Hand-in-hand" serial connection mode is realized through the CAT6 kinds of network cables, which is convenient for installation and maintenance;

12. Built-in full frequency limiter circuit;

13. The unit is a passive device, powered by the system host, and the input voltage is DC24V;

14. With camera tracking system & central control system, it can realize automatic camera tracking function;

15. Button sign-in function (used with software);

16. The chairman unit has the following conference control functions:

* In the application mode, the speech application function of the delegate can be approved; the speech unit of the delegate who is speaking can be forcibly closed;

* It is not limited by the number of speakers and the speech mode, and can be opened freely, regardless of the installation location;

* Can control the start/end of the voting & sign-in process;

Technical Parameter

Power supply	DC24V (Power supply by conference host)
Frequency response	20Hz-20KHz
Channel crosstalk	>80dB
Signal-to-noise ratio	>80dB
Maximum power consumption	3W
Sensitivity	-46dBV/pa
Frequency response	20Hz-20KHZ
Input impedance	2.2K
Headphone volume	10mW
Hole size	L 250* W 50 Narrow W 25(mm)
Dimensions (mm)	L 285* W 62 narrow W 36 (mm)
Color	Black Brushed Aluminum