



SC-3225C/SC-3225D Desktop Conference Chairman/Delegate Unit(With 3.5 Inch LCD Display And Voting Function)



Chairman unit SC-3225C



Delegate unit SC-3225D

Product Description

The desktop discussion unit is simple touch operation. Built-in speaker and headphone jack, clear sound quality, with volume adjustment knob, hand in hand connection through CAT6 (CAT6E) network cable. With speech discussion, timed speech, application for speech, meeting sign-in and LCD screen display.

Features

1. With digital audio stream processing technology, the sound quality is richer and clearer;
2. Avoid interference from RF signals such as telephones and other wireless signals when picking up sounds;
3. Novel, fashionable appearance, ergonomic design;
4. The unit with a 3.5-inch capacitive high-brightness LCD liquid crystal display, waterproof, durable, easy to clean, and can display in real time: microphone on/off, speaking time, perpetual calendar, clock, real-time check-in number, voting results and other information; voting & Relevant information in the sign-in process;
5. Supports the functions of timed speech, sign-in, 3-key/5-key voting; Multiple voting forms: yes/abstain/against; Election: choose one candidate from five candidates (1/2/3/4/5); Rating: scoring method (--/ -/0/+ /++);
6. The "hand in hand" serial connection mode is realized through the CAT6 network cable
7. Cardioid directional condenser pickup, with two-color indicator light, red when speaking, flashing green when applying to speak, and removable during recess;
8. \$ 3.5mm stereo headphone jack to connect headphones, high-fidelity speakers, adjustable volume;
9. Suppress howling function to prevent sound from returning;



10. With camera tracking system & central control system, it can realize automatic camera tracking function;

11. Microphone stem L: 420mm (standard configuration);

12. The unit is a passive device, powered by the system host, and the input voltage is DC24V.

13. The delegate unit has the function of applying for speech; It is controlled by the chairman unit, and the chairman unit initiates or stops voting;

14. The chairman unit has the following conference control functions:

- * Approval of the speech application function of the representative;

- * The speaking unit of the representative who is speaking can be forcibly closed;

- * It is not limited by the number of speakers and the speaking mode, and can be opened freely and is not limited by the installation position.

Technical Parameter

Power supply	DC24V (Power supply by conference host)
Frequency response	20Hz-20KHz
Channel crosstalk	>80dB
Signal-to-noise ratio	>80dB
Maximum power consumption	3W
Sensitivity	-46dBV/pa
Frequency response	20Hz-20KHZ
Input impedance	2.2K
Headphone volume	10mW
Dimensions (mm)	215mm×130mm×47mm
Color	Black Brushed Aluminum