

## SC-3600M Full-Digital Wireless Audio Conference Controller



### Functional features

- 1.Full-digital wireless audio conference system.
- 2.255 conference units can be connected within the signal coverage.
- 3.Digital wireless processing of audio and control signals with 8 communication IP and 160 communication ID option.
- 4.Strong anti-interference ability, increase data confidentiality, prevent malicious radio interference.
- 5.The system is designed with 6 channels, each channel has 60 channels for selection, and the host can disable any channel at any time.
- 6.The number of simultaneous speakers is 1-6 (the chairman unit and the representative unit can be freely combined).
- 7.Working content of 240 \* 128LCD large display screen, hierarchical menu design, simple and clear operation.
- 8.Three kinds of speech simulation settings: first-in first-out mode, chairman's special speech mode and limited speech.
- 9.Intelligent power management system, after the host is powered off, each unit will automatically shut down to reduce battery consumption.
- 10.Connect the video head to realize the real-time video tracking function, and support 4-channel camera signal input and 2-channel video output.
- 11.RS232 port can be connected to the central control, making the conference equipment intelligent.
- 12.Multiple PTZ machine control protocols, strong compatibility: Pelco \_ P VISCA \_ SONY-D70 Pelco \_ D protocol.
- 13.Communication distance: 130-150m.
- 14.Receiving distance: 100-120m in open environment, 60-80m in complex environment.

**Technical parameters**

Model	SC-3600M
Power source	DC12-17V
Receive sensitivity	-105dBm
Signal to noise ratio	>90dB
Distortion	<0.05% dB
Maximum frequency deviation	±45KHz
Effective working distance	≥ 100m
Number of session channels	6×64
Power	6.5W