



SC-3751C/SC-3751D Smart Full-Digital Conference Chairman /Delegate Unit (With Voting, 3.5-inch Screen)



Features:

1. Full digital conference technology, simple and strong anti-static desktop function design, in line with ergonomics, very modern sense of science and technology;
2. With a 3.5-inch touch screen, it can display speech time, speech timing, perpetual calendar, conference call service and other functions;
3. Adopt light touch keys, accurate positioning, rapid control, no mechanical keys, no wear, unlimited life;
4. Adopt the design of aluminum alloy integrated square microphone stem, and adopt the principle of sound interference, which has excellent super-directional performance;
5. Multi-functional conference speech unit integrating speech discussion, video tracking, voting and conference service;
6. DSP digital processing and transmission technology is adopted to overcome the problem of long-distance transmission attenuation. The six-core cable distance can reach 250 meters, and the network cable distance can reach 150 meters.
7. The chairman has a priority button, which can quickly close the delegate unit. The delegate unit can be set as a VIP unit. The VIP unit is not limited to speak and will not be opened and closed by other delegate units.
8. 24V power supply is provided by the conference controller, with low power consumption design, and 20 conference units can be connected in a single way;
9. Adopt digital strong anti-interference technology to ensure that the equipment in the venue is not interfered by mobile phones, Bluetooth, radio, WiFi and other signals;
10. The camera tracking function is available with the conference controller, which can be preset through the conference controller, control keyboard or PC software;
11. The system has first-in first-out, limited mode, speech application and other modes, and the number of speakers can be set from 1 to 6;



12. Designed with advanced electrostatic isolation technology to avoid static electricity even in dry environments and regions;

13. Live "hot plug" function is available between units, so that the safety of the system is more guaranteed;

14. Mic unit equipment adopts non-compressed audio transmission technology, 48K sampling rate, 20Hz-20KHz bandwidth, perfect sound quality; With low delay technology, the output from microphone sound to power amplifier is less than 10 ms; Long-distance high-fidelity pickup, with effective pickup distance greater than 50cm;

15. The system adopts the ID addressing mode, and the conference management software or the conference controller defines the ID number of the unit to avoid ID number duplication;

Technical parameters:

Power consumption	1.8W
System capacity	15 sets of six-core unit in single channel, which can be expanded to 51200 sets
Display screen	3.5 inch TFT contact display
Display menu	Chinese and English (customizable)
Frequency response	20Hz~20KHz
Signal to noise ratio	>90dB
Dynamic range	96dB
Channel separation	102dB
Total harmonic distortion	< 0.05%
Microphone type	Imported gold film pickup head
Microphone sensitivity	(-42dBV/Pa)
Operating voltage	24V DC $\pm$ 5%
Operating current	40mA $\pm$ 5%
Connection mode	Junction box
Number of units on	1/2/3/4/5/6
Equivalent noise	20dBA(SPL)
Maximum sound pressure level	125dB(THD $\angle$ 3%)
Mic stem L	200mm
Unit connection port	6-core DIN
Net weight	0.8kg
External dimensions	127 × 97 × 57mm (excluding the MIC stem)