



**SC-3754C/SC-3754D**

## **Full-digital Wireless Conference Chairman/Delegate Unit**



### **Features:**

1. Simple and stable countertop design with strong antistatic function, which conforms to ergonomics and has a sense of modern science and technology; Made of high-strength tempered glass, the appearance is very textured.
2. WiFi communication technology, 5G frequency full digital frequency hopping (DSSS) modulation communication technology intelligent frequency conversion, through the wireless audio data modulation algorithm, to achieve high-speed transmission of audio without compression, to ensure that the audio delay is less than 5.5mS; It can be mixed with the wired unit at the same time, which is flexible and convenient.
3. Adopt high-strength anti-scratch tempered glass surface, light touch keys, accurate positioning, rapid control, no mechanical keys, no wear, unlimited life;
4. Gooseneck condenser microphone stem, professional large capacitor core, extremely high sensitivity and voice clarity, with speaking ring red and green two-color indicator.
5. The chairman has a priority button, which can quickly close the delegate unit.
6. Support the functions of key sign-in and supplementary sign-in, and dynamic display of data; Have registered and anonymous sign-in;
7. The system has first-in first-out, last-in first-out, chairman computer permission, free discussion, limited mode, and the number of speakers can be set;
8. Support the automatic startup function of the speech unit, automatically turn off the power supply when there is no speech, and extend the battery life. The chairman and delegate units can be used normally during charging.
9. With the camera, the camera can be automatically tracked through the conference controller, control keyboard or PC software preset;
10. With the controller computer, the system can expand 4096 delegate units.
11. Adopt digital strong anti-interference technology to ensure that the equipment in the venue is not interfered by mobile phones, Bluetooth, radio, WiFi and other signals;



12. The capacity of the built-in lithium battery is not less than 4100mA. When fully charged, it can be used continuously for not less than 40 hours, and the standby time is not less than 60 hours.

13. Designed with advanced electrostatic isolation technology to avoid static electricity even in dry environments and regions;

14. With intelligent audio detection function, when two adjacent units are close to each other, the audio will be automatically inverted and attenuated to ensure that there is no howling;

15. It has the function of band-pass filter, which can effectively filter out some useless noise components outside the audio frequency spectrum.

**Technical parameters:**

Frequency response	20Hz~20kHz
Wireless index standard	IEEE Draft 2.0802.11n
Battery output voltage	7.2V
Battery capacity	4100mAH
Net weight	1.1kg
External dimensions	127 × 97 × 57mm (excluding the MIC stem)