



SD-210H Dual 10-inch Two-way Linear Array Speaker
SD-210HD Single 18-inch Ultra-low Frequency Speaker



Features

High-performance compact three-frequency linear array, continuous high-power output; Advanced full horn design, with a very long projection distance; Wide frequency bandwidth, firm and fast integral suspension system, variable opening angle; Ergonomically designed and equipped with a dedicated air box for easy transportation and stacking; When installing, it can be installed in groups on the ground first. Hang in the whole group; Even in venues without subwoofers, the wide frequency bandwidth of this linear array can still meet the needs of sound reinforcement. The surface is sealed and rainproof, meeting the requirements of outdoor sound reinforcement; Whether it is a fixed installation project or a mobile performance, its versatility and scalability can be widely used. It is suitable for a wide range of venues, theaters, cinemas and entertainment venues. Commercial performances and other large-scale sound reinforcement required venues; Innovative technology and rigorous manufacturing, powerful sound effects and wide dynamic range changes are sure to impress you.

Technical parameters

Model	SD-210H	SD-210HD
Bass unit	Dual 10-inch bass 300W/16 Ω , neodymium magnet	100-core voice coil, 800W/8 Ω , 220 magnet
Treble	1*44mm tweeter, 44-core voice coil, neodymium magnet	
Horn material	Fiberglass	
Speaker material	18 mm birch board	25mm birch board
Surface treatment	Black gold sand paint	Black gold sand paint
Sound box iron net	1.5mm porous steel mesh lined with dustproof cotton	2.0mm porous steel mesh lined with dustproof cotton
Hanging accessories	Combined suspension	Combined suspension
Wiring mode	2 x NL4 Speakon	2 x NL4 Speakon



Frequency response range	45Hz-20KHz	26Hz-500Hz
Sensitivity	113dB	98dB
Rated power	650W	800W
Maximum SPL	133dB	127dB
Resistance	8 (Ω)	8 (Ω)
Coverage Angle	110°×10° (H×V)	
Size	275×892×474mm (L×W×H)	521×893×575mm (L×W×H)
Weight	32Kg	42Kg