



SD-6BM/SD-8BM/SD-12BM

6-channel/8-channel/12-channel Mixer(with USB playback)



Features

1. 6/8/12-way mono input + 1 stereo channel
2. With Bluetooth connection, USB playback/recording function
3. The highest support for 24-bit/48kHz specification recording
4. LCD colour screen display, with 99 kinds of DSP effects
5. USB independent playback channel
6. 4-way bus (BUS): main output + studio output + recording output
7. 1 set of auxiliary sends and 1 set of auxiliary returns
8. 60MM high-precision logarithmic attenuation fader
9. Built-in 48V phantom power supply, built-in 80V-240V wide-voltage power supply

Technical parameters

Model	SD-6BM	SD-8BM	SD-12BM
Mono input channel	6 channel	8 channel	12 channel
Mono insert channel	6 channel	8 channel	12 channel
Total Harmonic Distortion Rate	<0.0007%		



Attenuation (Crosstalk)	-82dBu		
Frequency Response	20Hz~20KHz \pm 1dB		
Mic Input Maximum Level	+22dBu		
Channel Input Return Maximum Level	+22dBu		
Main Mix Maximum Level	+28dBu		
Other Input Maximum Level	+22dBu		
Mic Input Impedance	2.5K Ω		
Channel Input Return Impedance	2.5K Ω		
Other Input Impedance	10K Ω		
Record Output Impedance	1.1K Ω		
Other Output Impedance	120 Ω		
Weight	2.9kg	3.4kg	4.45kg
Dimensions (W×D×H)	305×335×78mm	360×335×78mm	470×335×78mm